

Product data sheet

Specifications



Electronic time delay auxiliary contact block, TeSys K, 1C/O, on delay 1-30s, front, control 24...48V AC/DC

LA2KT2E

Main

Range	TeSys
Product name	TeSys K
Product or component type	Time delay auxiliary contact block
Device short name	LA1
Range compatibility	TeSys K LC1K TeSys K CA2K TeSys K CA3K TeSys K CA4K
Mounting location	Front
Pole contact composition	1 C/O
Contacts operation	Time delay
Timer type	On delay
Time delay range	1...30 s
[Ue] rated operational voltage	24...48 V AC/DC for control circuit 240 V AC for signalling circuit
Rated operational voltage limits	0.85...1.1 Uc
[Ith] conventional free air thermal current	2 A for signalling circuit
Standards	EN/IEC 60947-5-1
Product certifications	CE UKCA

Complementary

Insulation resistance	> 10 MΩ
Connections - terminals	Slip-on terminals
Reset time	1.5 s during time delay 0.5 s after time delay
Height	27 mm
Width	38 mm
Depth	38 mm
Net weight	0.04 kg

Environment

Environmental characteristic	Normal environment
IP degree of protection	IP20 conforming to IEC 60529

Protective treatment	TC conforming to IEC 60068
Ambient air temperature for operation	-10...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	4.800 cm
Package 1 Length	4.800 cm
Package 1 Weight	40.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	70
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.110 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint

4

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	8a21c0d1-be95-4e83-b703-1e8075e942f8
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

