

# Product data sheet

Specifications

SQUARE D



NEMA Motor Starter and contactor, Type S, auxiliary contact, 1 NO contact, external, field convertible

9999SX6

Product availability: Stock - Normally stocked in distribution facility

## Main

|                |                          |
|----------------|--------------------------|
| Product Range  | Type S                   |
| Component type | Auxiliary Contact Module |
| Used with      | contactor starter        |

## Complementary

|                               |                                                                                                                                                                                                                                                           |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NEMA size                     | 0<br>3<br>6<br>7<br>4<br>5<br>1<br>00<br>2                                                                                                                                                                                                                |
| Auxiliary contact composition | 1 NO                                                                                                                                                                                                                                                      |
| [Uc] control circuit voltage  | <= 600 V AC 50/60 Hz                                                                                                                                                                                                                                      |
| Rated breaking capacity       | 6 A 120 V AC inductive control circuit UL 508<br>3 A 240 V AC inductive control circuit UL 508<br>1.2 A 600 V AC inductive control circuit UL 508<br>1.5 A 480 V AC inductive control circuit UL 508<br>10 A <= 600 V AC resistive control circuit UL 508 |
| Height                        | 1.5 in (38.1 mm)                                                                                                                                                                                                                                          |
| Width                         | 3 in (76.2 mm)                                                                                                                                                                                                                                            |
| Depth                         | 4.5 in (114.3 mm)                                                                                                                                                                                                                                         |
| Product Weight                | 0.20 lb(US) (0.09 kg)                                                                                                                                                                                                                                     |

## Environment

|                        |                                   |
|------------------------|-----------------------------------|
| Product Certifications | CSA<br>UL Listed<br>UL Recognized |
|------------------------|-----------------------------------|

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10CP121761 |
| Discount Schedule | 0CP1         |
| GTIN              | 785901733300 |
| Returnability     | Yes          |
| Country of origin | MX           |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Nbr. of units in pkg.        | 1                       |
| Package 1 Height             | 1.500 in (3.810 cm)     |
| Package 1 Width              | 3.100 in (7.874 cm)     |
| Package 1 Length             | 4.600 in (11.684 cm)    |
| Package weight(Lbs)          | 3.200 oz (90.718 g)     |
| Unit Type of Package 2       | CAR                     |
| Number of Units in Package 2 | 10                      |
| Package 2 Height             | 5.700 in (14.478 cm)    |
| Package 2 Width              | 6.800 in (17.272 cm)    |
| Package 2 Length             | 8.000 in (20.320 cm)    |
| Package 2 Weight             | 2.359 lb(US) (1.070 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

| Materials and Substances               |                                                                                                                                                                                                                                                                                             |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                                                                                                                                                                         |
| Packaging without single use plastic   | No                                                                                                                                                                                                                                                                                          |
| EU RoHS Directive                      | <a href="#">Compliant</a>                                                                                                                                                                                                                                                                   |
| REACH Regulation                       | <a href="#">Free of Substances of Very High Concern above the threshold</a>                                                                                                                                                                                                                 |
| California proposition 65              | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture |                                                                                                                              |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Circularity Profile      | No need of specific recycling operations                                                                                     |
| Take-back                | No                                                                                                                           |
| WEEE Label               | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Technical Illustration

Dimensions

