

## Commercial GFCI Receptacles

The new commercial GFCI receptacles feature an attractive new aesthetic look. A single rectangular LED indicator visually displays the device's ability to provide protection: green indicates power, red indicates a trip, and flashing red indicates end of life. Redesigned test and reset buttons provide a flush look and feel to the face of the receptacle.

Patented AUTOGUARD® self-test technology includes exclusive Closed Loop Active Detection (CLAD). Our advanced microcontroller identifies and isolates true ground fault conditions from transient events, harmonics, and other anomalous building noise, improving interoperability. Tamper-resistant (TR) listed models feature our patented shutter design for protection. Weather-resistant (WR) and combination tamper-resistant/weather-resistant (TRWR) models are also available.

Use Bryant commercial GFCI receptacles for commercial installations in airports, office buildings, schools, and other facilities.

- Single LED indicator—power (green), trip ground fault (red), and end of life (flashing red)
- Patented AUTOGUARD® self-test and power denial technology
- Available in tamper-resistant and weather-resistant versions
- Available in black, brown, gray, white, ivory, light almond and red



# Commercial GFCI Receptacles

## ORDERING INFORMATION

Description	Color	15A	20A
Commercial grade ground fault receptacles, standard	Brown	GFR15	GFR20
	Black	GFR15BLK	GFR20BLK
	Gray	GFR15GRY	GFR20GRY
	Ivory	GFR15I	GFR20I
	Light Almond	GFR15LA	GFR20LA
	Red	GFR15R	GFR20R
	White	GFR15W	GFR20W
Commercial grade ground fault receptacles, tamper-resistant	Brown	GFRT15	GFRT20
	Black	GFRT15BLK	GFRT20BLK
	Gray	GFRT15GRY	GFRT20GRY
	Ivory	GFRT15I	GFRT20I
	Light Almond	GFRT15LA	GFRT20LA
	Red	GFRT15R	GFRT20R
	White	GFRT15W	GFRT20W
Commercial grade ground fault receptacles, weather-resistant	Brown	GFRWR15	GFRWR20
	Black	GFRWR15BLK	GFRWR20BLK
	Gray	GFRWR15GRY	GFRWR20GRY
	Ivory	GFRWR15I	GFRWR20I
	Light Almond	GFRWR15LA	GFRWR20LA
	Red	GFRWR15R	GFRWR20R
	White	GFRWR15W	GFRWR20W
Commercial grade ground fault receptacles, tamper and weather-resistant	Brown	GFRTW15	GFRTW20
	Black	GFRTW15BLK	GFRTW20BLK
	Gray	GFRTW15GRY	GFRTW20GRY
	Ivory	GFRTW15I	GFRTW20I
	Light Almond	GFRTW15LA	GFRTW20LA
	Red	GFRTW15R	GFRTW20R
	White	GFRTW15W	GFRTW20W



## TECHNICAL INFORMATION

Ratings		Certifications		Construction	
Amperage	15 Amp/20 Amp	UL Listing	E41978 Fed Spec	Termination	Back and Side
Feed-through	20 Amp	UL Std 498	Receptacle	Terminal	#14 to #10AWG
Voltage	120V AC (-15%, +10%)	UL Std 943	GFCI	Grounding	Autoground Clip
Frequency	60 Hz	UL Std 943	Dust Resistant	Power Indicator	Solid Green
Dielectric	Withstand 1,500V	UL Std 943	Corrosion Resistant	GF/Trip Indicator	Solid Red
Flammability	V0 per UL 94	NEC®/CEC®	TR, WR Resistant	End of Life	Flashing Red
Operating Temp	(-35°C to 66°C)	CSA Listing	LR24886	Contacts/Bridge	Nickel Plated
Trip Level	(4mA to 6mA) .025 sec.	CSA Std	C22.2 No. 42	Printed Circuit Board	Conformal Coat
Short Circuit	10,000 Amps	CSA Tech	No. M-02A	Scored Bridge	OEM Installations

### Code and Standard Compliance

#### National Electric Code®

Compliant with NEC® 406.12 and NEC® 517-18c for Tamper-Resistance

Compliant with NEC® 406.9 for Weather Resistance

#### Industry Standards

NEMA WD6, ANSI C-73, NOM, National Electric Code, Canadian Electric Code



A proud member of the Hubbell family.

©2024 Hubbell Incorporated. All rights reserved.

Bryant and the Bryant logo are registered trademarks or trademarks of Hubbell Incorporated.

All other trademarks are the property of their respective owners.

40 Waterview Drive, Shelton, CT 06484

hubbell.com/bryant | (800) 323-2792

EP-BRY-SF-EN-02174 4/24