

# Product data sheet

Specifications



Add-on residual current device,  
Multi9 Vigi C60, 2P, 63A, AC type,  
instantaneous, 30mA, 230/240VAC

M9V11263

**Product availability:** Stock - Normally stocked in distribution facility

## Main

Range	Multi9
Product or Component Type	Add-on residual current device
Device short name	Vigi C60
Range compatibility	Multi9 Multi9 C60 C60N Multi9 Multi9 C60 C60L Multi9 Multi9 C60 C60H Multi9 Multi9 C60 C60CTRL
Poles description	2P
Line Rated Current	63 A EN/IEC 61009-1
Network type	AC
Network Frequency	50 Hz
[Ue] rated operational voltage	230/240 V AC 50 Hz
Earth-leakage sensitivity	30 mA EN/IEC 61009-1
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC
9 mm pitches	4
Standards	EN/IEC 61009-1 EN/IEC 61009-2-1

## Complementary

Residual current tripping technology	Voltage independent
[Ui] rated insulation voltage	500 V AC 50 Hz EN/IEC 61009-1
[Uiimp] rated impulse withstand voltage	4 kVEN/IEC 61009-1
Local signalling	Fault indication
Mounting Mode	Clip-on
Mounting Support	DIN rail
Electrical connection to mcb	By screws
Height	3.4 in (87 mm)
Width	1.4 in (36 mm)
Depth	2.9 in (74 mm)
Net Weight	5.3 oz (150 g)
color	Gray

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Connections - terminals</b>	Tunnel type terminal bottom) 0.002...0.05 in <sup>2</sup> (1...35 mm <sup>2</sup> ) - rigid Tunnel type terminal bottom) 0.002...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) - flexible Tunnel type terminal bottom) 0.002...0.04 in <sup>2</sup> (1...25 mm <sup>2</sup> ) - flexible with ferrule
<b>Wire stripping length</b>	0.6 in (14 mm) for bottom connection
<b>Tightening torque</b>	31.0 lbf.in (3.5 N.m) bottom

## Environment

<b>IP degree of protection</b>	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
<b>Pollution degree</b>	3 IEC 61009
<b>Electromagnetic compatibility</b>	8/20 $\mu$ s impulse withstand, 250 A EN/IEC 61009-1
<b>Tropicalisation</b>	2 IEC 60068-1
<b>Relative humidity</b>	95 % 131 °F (55 °C)
<b>Ambient air temperature for operation</b>	23...140 °F (-5...60 °C)
<b>Ambient Air Temperature for Storage</b>	-40...140 °F (-40...60 °C)

## Ordering and shipping details

<b>Category</b>	US10DE200908
<b>Discount Schedule</b>	ODE2
<b>GTIN</b>	3606480684548
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	3.425 in (8.700 cm)
<b>Package 1 Width</b>	3.425 in (8.700 cm)
<b>Package 1 Length</b>	4.724 in (12.000 cm)
<b>Package weight(Lbs)</b>	6.596 oz (187.000 g)
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	27
<b>Package 2 Height</b>	11.811 in (30.000 cm)
<b>Package 2 Width</b>	11.811 in (30.000 cm)
<b>Package 2 Length</b>	15.748 in (40.000 cm)
<b>Package 2 Weight</b>	12.253 lb(US) (5.558 kg)

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **81**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **01327915-acdb-4543-8666-60c841ff9e81**

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile **No need of specific recycling operations**

Take-back **No**

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.