



SKU: PICS-63

UPC: 0783669232868

Features & Benefits:

Description: Aluminum Insulated Service Entrance Sleeve, Dual Rated, Main Conductor Range 4 Sol - 6, Tap Range 6 Sol - 8, Blue Color Code, Die Index ND-BG

Specs

Additional Class Attributes

| | |
|-------------------------|----------|
| Barrel Marking | Ink |
| Barrel Type | Standard |
| Flared End | No |
| ILSCOs Die Index Number | ND-BG |

Dimensions

| | |
|----------------|--------|
| Height (IN) | 0.72 |
| Height BX (IN) | 2.75 |
| Height (mm) | 18.288 |
| Length (IN) | 2.81 |
| Length (mm) | 71.374 |
| Weight (LB) | 0.055 |
| Weight BX (LB) | 2.997 |
| Width (IN) | 0.72 |
| Width BX (IN) | 6 |
| Width (mm) | 18.288 |

Material and Finish

| | |
|---------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish | NA |
| Insulation Material | Nylon |
| Material | Aluminum |

Additional Technical Specifications

| | |
|----------------|-------|
| Conductor Type | Solid |
|----------------|-------|

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 50 |
| Direct Burial | No |
| Dual Rated | Yes |
| NEMA Code | 0-000-1 |
| UPC Code | 78366923286 |



Bolt and Screw Sizes

| | |
|-------------------------|----|
| Mounting Bolt/Stud Size | NA |
|-------------------------|----|

Testing Standards

| | |
|--------------------|---|
| ANSI Specification | ANSI C119.4 |
| CSA File Number | NA |
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| RUS Listed | Yes |
| UL Control Number | NA |
| UL File Number | NA |

Environment and Temperature

| | |
|--------------------|----|
| Temperature Rating | NA |
|--------------------|----|

Color

| | |
|----------------------|-------|
| Color | Black |
| Color Code | Blue |
| Color Code Secondary | Green |

Conductor Ranges

| | |
|--|---------------|
| Conductor Range ACSR (Secondary, tap, load) | 6 ACSR |
| Conductor Range ACSR (primary, run, main, line) | NA |
| Conductor Range AL Solid (Secondary, tap, load) | 6 Sol - 8 Sol |
| Conductor Range AL Stranded (Primary, run, main, line) | 4 Str - 6 Str |
| Conductor Range AL Stranded (Secondary, tap, load) | 6 Str - 8 Str |
| Conductor Range CU Solid (Primary, run, main, line) | 4 Sol |
| Conductor Range CU Solid (Secondary, tap, load) | 6 Sol - 8 Sol |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 6 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | 6 Str - 8 Str |
| Conductor Range AL Solid (Primary, run, main, line) | 6 Sol - 8 Sol |