

Product data sheet

Characteristics

MPZB22T2F

Unit substation, Mini Power-Zone, bolt on, 22.5kVA, 3 phase, 480V primary, 208Y/120V secondary, 18kA, CC



Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	CC
Insulation Temperature	365 °F (185 °C)
Phase	3 phase
Primary Voltage	480 V
Secondary Voltage	208Y/120 V
Full Capacity Taps	2 5 % FCBN
Power Rating	22.5 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Circuit Breaker Type	FAL34070 primary main breaker 70 A QO380 secondary main breaker 80 A QO/QOB feeder breaker 60 A
Interior Type	NQ Panelboard interior
Number of Spaces Available	27
Number of Circuits	27
Enclosure Type	NEMA 3R hot-rolled steel

Ordering and shipping details

Category	16276-MPZ BOLT-ON BRANCH CB
Discount Schedule	PE2
GTIN	785901084341
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.49 in (36.8 cm)
Package 1 Width	29.13 in (74.0 cm)
Package 1 Length	51.26 in (130.2 cm)
Package 1 Weight	670.00 lb(US) (303.907 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration

RoHS exemption information

Yes

PVC free

Yes

Contractual warranty

Warranty

18 months
