



Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	1P
Circuit Breaker Type	Tandem
Ratings	HACR rated
Electrical Connection	Pressure plate

Complementary

Interrupt Rating	10 kA 120/240 V AC 50/60 Hz
Number of Panel Spaces	1
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening Torque	24.78 lbf.in (2.8 N.m)
Height	3.23 in (82 mm)
Width	0.75 in (19 mm)
Depth	2.91 in (74 mm)
Net Weight	0.35 lb(US) (0.159 kg)

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details


Category	00004-QO,QOT 10-30A 1P;10-60A 2P
Discount Schedule	DE2A
GTIN	785901418085
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.30 in (8.382 cm)
Package 1 Width	0.70 in (1.778 cm)
Package 1 Length	3.40 in (8.636 cm)
Package 1 Weight	5.61 oz (159.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.80 in (9.652 cm)
Package 2 Width	0.70 in (1.778 cm)
Package 2 Length	7.60 in (19.304 cm)

Package 2 Weight	3.36 lb(US) (1.524 kg)
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	8.20 in (20.828 cm)
Package 3 Width	8.30 in (21.082 cm)
Package 3 Length	19.80 in (50.292 cm)
Package 3 Weight	34.95 lb(US) (15.853 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------