

Plugs and Bushings

1 INCH SQUARE HEAD PLUG



Catalog Number PRPLG35
UPC 784011209637

Description

PLG style plugs are used to close unused conduit hubs. They are available with either recessed square drive sockets or raised square drive heads.



Application

- Used to close unused conduit hubs

Features

- Used to close unused conduit hubs
- Available with raised square drive heads

General Information

| | |
|-----------------|--|
| Trade Size | 1 |
| Material | FERROUS METAL |
| Material | FERROUS METAL |
| Exterior Finish | Polyurethane coating on non-thread surfaces for corrosion protection |

Dimensions

Nominal Weight (Pounds) 0.2

Standards

| | |
|---------|--|
| NEC/CEC | Class III |
| NEC/CEC | Class II, Division 1, Groups E, F, G |
| NEC/CEC | Class II, Division 2, Groups F, G |
| NEC/CEC | Class I, Division 1 & 2, Groups A, B, C, D |

Technical Specification Documents

| | |
|-----------------------------------|----------------------|
| Specification Guide (1995 Master) | AVAILABLE ON WEBSITE |
| Specification Guide (2004 Master) | AVAILABLE ON WEBSITE |
| Installer Certification and Tools | AVAILABLE ON WEBSITE |
| Chemical Resistance Charts | AVAILABLE ON WEBSITE |
| Performance Specifications | AVAILABLE ON WEBSITE |

Technical Information

| | |
|-----------------------|--------------------|
| Fitting Configuration | SQUARE HEAD |
| Fitting Type | PLUG |
| Product Category | FITTING |
| Product Family | Plugs and Bushings |

Notes

- All REC, RE, and PLGs meet Class I, Division 1 & 2, Groups C, D. REs & PLGs meet the above standards only when used in conjunction with hazardous location fittings.
- Suitable for Groups A & B.