

QO200TR

Enclosed molded case switch, QO, 60A, 2 pole, 240VAC, 22kA, air conditioning, NEMA 3R



Main

Product Type	Enclosed molded case switch Weatherproof enclosure
Range of Product	QO

Complementary

Current Rating	60 A
Interrupt Rating	22 kA 240 V AC
Number of Phases	1 phase
Enclosure Rating	NEMA 3R outdoor
Breaker Compatibility	Circuit breaker QO 2P
For Use With	Air conditioner
Product Certifications	UL Listed
Indoor/Outdoor Use	Enclosed outdoor
Surface Finish	Baked enamel Gray
Voltage Rating	240 V AC
Ambient Air Temperature for Operation	104 °F (40 °C)
Height	6.50 in (165 mm)
Width	4.65 in (118 mm)
Depth	3.90 in (99 mm)
Product Weight	3.00 lb(US) (1.361 kg)

Ordering and shipping details

Category	00044-A/C DISC & PULL-OUTS
Discount Schedule	DE2A
GTIN	785901535966
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.50 in (8.89 cm)
Package 1 Width	4.20 in (10.668 cm)
Package 1 Length	6.50 in (16.51 cm)
Package 1 Weight	3.00 lb(US) (1.361 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	10

Package 2 Height	7.10 in (18.034 cm)
Package 2 Width	9.80 in (24.892 cm)
Package 2 Length	19.80 in (50.292 cm)
Package 2 Weight	30.35 lb(US) (13.767 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	400
Package 3 Height	42.00 in (106.68 cm)
Package 3 Width	40.00 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)
Package 3 Weight	1270.00 lb(US) (576.062 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------