

PVC Coated Nipples

3/4XCLOSE PVC COATED NIPPLE



Catalog NumberPRHNIP-3/4XCL

UPC784011210046

Description

Factory-threaded PVC coated nipples save time and money in the field. Electrical continuity is maintained across assembled joints.

Application

- Factory-threaded PVC coated nipples save time and money in the field

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 12 trade sizes from 1/2" through 6"
- 11 standard lengths in available: Close, 2" to 12"
- Made to order lengths available - Call for quote
- Color-coded thread protector caps for quick identification of conduit size



General Information

Trade Size	3/4
Material	STEEL
Material	STEEL
Exterior Finish	A nominal .040 inch (40 mil) Gray PVC Coating
Interior Finish	A nominal .002 inch (2 mil) red urethane
Thread Finish	A clear urethane coating over Hot Galvanized Steel
Thread Protector Color	Red

Dimensions

Diameter With Coating (Inches)

1.13



Internal Inside Diameter (Inches)	0.836
Length (Inches)	1-3/8
Metric Size Designators	21
Outside Wall Thickness (Inches)	0.107
Pipe Size (Inches)	3/4

Standards

CSA CERTIFIED	C22.2 No. 45
UL 6	E2314

Technical Specification Documents

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

Technical Information

Fitting Configuration	CLOSE
Fitting Type	NIPPLE
Product Category	CONDUIT
Product Family	PVC Coated Nipples

Notes

- The exteriors of certain short nipples are coated with urethane in lieu of PVC, dictated by the manufacturing process as well as assembly considerations.