

Specifications



Eaton FH58

Eaton A200/B100 heater, Used with Starter Sizes 1, and 2, A200/B100 Heater, NEMA, Ambient .25-.27, .29-.31A, Non-Comp .24-.25, .28-.30A, Used with Starter Sizes 1, and 2, Type A and B, Thermal and Fast Trip

General specifications

PRODUCT NAME	Eaton A200/B100 heater
CATALOG NUMBER	FH58
UPC	786678670430
PRODUCT LENGTH/DEPTH	2.1 in
PRODUCT HEIGHT	0.8 in
PRODUCT WIDTH	1.3 in
PRODUCT WEIGHT	0.03 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	CSA Certified UL Listed
CATALOG NOTES	Select heater coils based on full load current(FLA) shown on motor nameplate. Heater coils are rated to protect 40 degree C rise and a service factor of 1.15, Single-Phase requires 2 heaters, Three-Phase Requires 3 heaters
GLOBAL CATALOG	FH58

Product specifications

SPECIAL FEATURES	Used with Starter Sizes 1, and 2
TYPE	A200/B100 Heater
USED WITH	Used with Starter Sizes 1, and 2
DESIGN	NEMA
FULL LOAD CURRENT RANGE	Ambient 0.25-0.27, 0.29-0.31 A, Non-Comp 0.24-0.25, 0.28-0.30 A
OVERLOAD RELAY	Type A and B
TRIP TYPE	Thermal and fast trip

Resources

CATALOGS	Motor Control and Protection, NEMA Manual Starters, Volume 5, Tab 3
INSTALLATION INSTRUCTIONS	Instructions for A200, A210, A250 size 6, two- or three-pole non-reversing or reversing motor controllers
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FH58

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

