



Representative Image

Catalog No. U035F2

Description: MW 30A GD ACD F PULLER 3HP STL N3R

UPC No 784567301021

Home > AC Disconnects > AC Disconnects

Metallic, 30A Fusible disconnects. Pullers are removable or reinstallable in the OFF position for user safety during equipment maintenance. Listed for use as service entrance.

Descriptors

Category	AC Disconnects
----------	----------------

Specifications

Phase	1
Amps	30 A
Enclosure	Metallic
Circuit Protection	Fused Pull-Out
Receptacles	None
AIC	10,000
Cabinet Size	5 X 7
Horse Power Rating	3
Neutral Bar	None
Unit Weight	2.5 lb
Volts	120/240

Classifications

Standard Package	6
Stock Class Code	Stock

Approvals

Certification	UL/CUL
---------------	--------

Publications

Title	Publication No.	Publication Type
AC Disconnects 6 pages. MET-006 Rev. B	MET-006A	Brochures
MIDWEST 30A GD AC DISCONNECT OUTLINE DRAWING MIDWEST 30A GD AC DISCONNECT PULLER-TYPE 3PH 240V 7.5HP FUSIBLE METALLIC N3R ENCLOSURE	U035F2	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.