

Control Power Transformer, 500va, PRI 208/277v, SEC 120v, Domestic,



Figure similar

Product brand name	Control Power Transformer
Design of the product	Control power voltage
Special product feature	Robust design
General technical data	
Weight [lb]	19.2 lb
Height x Width x Depth [in]	5.69 × 5.25 × 5.42 in
Ambient temperature [°F]	
• during operation	-4 ... +104 °F
Ambient temperature	
• during operation	-20 ... +40 °C
Country of origin	Mexico
Operating apparent output rated value	500 V·A
Enclosure	
Design of the housing	Open
Mounting/wiring	
Mounting position	Any
Mounting type	Surface mounting

Type of electrical connection at input for main current circuit	Screw-type terminals (touchsafe)
---	----------------------------------

Inputs/ Outputs

Input dimensions of primary voltage	208/277vac
Output dimensions of secondary voltage	120vac
Design of fuse holder of the secondary section	Require touchsafe cover
Phase number of the inputs	1
Electrical input frequency	50 ... 60 Hz
Input voltage _1	208 V
Input voltage _2	277 V
Phase number of the outputs	1
Electrical output frequency	60 ... 50 Hz
Output voltage _1 rated value	120 V
Certificate of suitability	UL / CSA

Further information

Industrial Controls - Product Overview (Catalogs, Brochures,...)

www.usa.siemens.com/iccatalog

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:MT0500F>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/US/en/ps/US2:MT0500F>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:MT0500F&lang=en

Certificates/approvals

<https://support.industry.siemens.com/cs/US/en/ps/US2:MT0500F/certificate>

last modified:

11/15/2019