

QOM2200MM

Main breaker, QO, 200A, 2 pole, 120/240VAC, 10kA, bolt on mount, for metering devices



Main

Product	Circuit breaker
Range	QO
Current Rating	200 A
Voltage Rating	120/240 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Ratings	Primary main breaker
Electrical Connection	Lugs
Frame Size	QOM2

Complementary

Interrupt Rating	10 kA 120/240 V AC 50/60 Hz
Wire Size	AWG 4...300 kcmil copper or aluminium
Tightening Torque	53.10 lbf.in (6 N.m) 0.01...0.10 in ² (4...65 mm ²) (AWG 12...AWG 2/0)
Height	5.59 in (142 mm)
Width	5.08 in (129 mm)
Depth	3.58 in (91 mm)
Net Weight	2.59 lb(US) (1.175 kg)
Load Center Type	Main breaker
Number of Phases	1 phase
For Use With	QO load center
Breaker compatibility	Load center QO

Environment

Certifications	UL Listed[RETURN]CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	00024-Q2 & QE METERING BREAKERS
Discount Schedule	DE2A
GTIN	785901765226
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.20 in (10.668 cm)
Package 1 Width	5.50 in (13.97 cm)
Package 1 Length	6.50 in (16.51 cm)
Package 1 Weight	2.59 lb(US) (1.175 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	468
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)

Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	1259.00 lb(US) (571.072 kg)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------