

## 316 Stainless Steel Drain, 1/2" NPT - Ex e Class I Div. 2 IP66/4X

By Killark

Catalog # [KDES60050](#)

316 Stainless Steel Drain, 1/2" NPT - Ex e Class I Div. 2 IP66/4X.



\*Representative Image

### Features

- Silicone O-ring supplied as standard and suitable for use in a -55°C to +80°C temperature range.
- 316 stainless steel.
- Internal 316 stainless steel locknut supplied as standard.
- When tightened to the proper torque the joint makes a hose down tight seal for type 4, 4X & IP66 application.

### General

Application	
Catalog Number	KDES60050
EU RoHS Indicator	Contact Manufacturer
Material	316 Stainless Steel
Operating Temperature Celcius	80
Max	
Operating Temperature Celcius	-55 °C
Min	
Operating Temperature Range Celcius	-55°C to 80°C
Series	KDE
Type	
UPC	783936121635

### Dimensions

Hub Size	1/2"
----------	------

### Certifications And Compliance

ATEX File Number	15ATEX3028X
CSA File Number	2715851
Hazardous Rating(s)	Class I, Divisions 2, Groups A, B, C, D Class I, Zones 1 & 2 Class II, Divisions 1 & 2, Groups E, F, G Class III, Divisions 1 & 2
IECEx File Number	15.0002X
Nema Rating	3, 4, 4X

### Logistics

Carton Quantity	10
-----------------	----

### Product Assets

<a href="#">Catalogs - Killark Catalog</a>
<a href="#">Certifications - KDE Series CSA Certification</a>
<a href="#">Certifications - KDE Series Drain Breathers IECEx Certification</a>
<a href="#">Certifications - KDE Series ATEX Certificate</a>
<a href="#">Certifications - KDE Series Declaration of Conformity</a>
<a href="#">Customer Notices - Prop 65 Notice</a>
<a href="#">Installation Manuals - KDE Series IOM K1458</a>



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
KILL\_CA-KDES60050-SPEC-EN | REV 6/2024