

Straight Blade Devices  
20A, 125V, 2 Pole, 3 Wire Grounding  
MRI Duplex Receptacle

# HUBBELL



## Features

- All non-ferrous for MRI labs
- One-piece nickel-plated brass integral ground strap
- Unique bypass contact design
- I.D. marking surface helps in quick circuit identification

## Ordering Information

Description	Device Color	UPC	Catalog Number
Flush, thermoplastic polyester face. Back and side wired.	White	783585148670	HBL8300WMRI

## Listings

UL Listed to UL498 File No. E2186  
Certified to CSA, C22.2, No. 42 File 285  
Fed. Spec. W-C-596  
NEMA® WD-6 Compliant



## Accessories

Wallplate or Weatherproof Cover Duplex Opening

## Specifications

Face	PBT
Base	PBT
By-Pass Power Contacts	.036". (.9) Nickel plated brass
Ground Contacts	.025 in. (.6) Brass
Clamp	Nickel plated brass
Terminal Screws	Plated brass
Mounting Strap	.050 in. (1.3) Nickel plated brass
Mounting Screws	Bronze

## Performance

### Electrical

Current Interrupting Certified for current interrupting at full rated current  
Dielectric Voltage Withstands 2,000V minimum

### Mechanical

Product Identification Ratings are a permanent part of the device  
Terminal Accommodation #12-#10 AWG stranded or solid copper wire only  
Terminal Identification Terminals identified in accordance with UL 498 and CSA

### Environmental

Flammability UL 94V-2  
Operating Temperatures Maximum continuous 75°C; minimum -40°C (w/o impact)

## Resources

[eCatalog](#)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.