

TradeSelect, Decorator Switch,
Residential Grade, Rocker Switch,
General Purpose AC, 4 Way, 15A
120/277V AC, Push Back and Side
Wired

By Hubbell Wiring Device-Kellems
Catalog # [RSD415W](#)

TradeSELECT® Decorator Switch, Residential Grade, Rocker
Switch, General Purpose AC, Four Way, 15A 120/277V AC, Push
Back and Side Wired.

Features

- Smooth, quiet rocker
- Self-grounding feature is standard
- Ultrasonically welded cover and base

Performance

- Electrical - Dielectric voltage - Withstands 1,500V AC minimum for 1 minute
- Electrical - Endurance - 30,000 cycles minimum
- Electrical - Max. working voltage - 120V
- Electrical - Overload - 1.5 times rating
- Environmental - Flammability - UL V0
- Environmental - Operating temperatures - Maximum continuous 60°C
- minimum -20°C (without impact)
- Mechanical - Terminal accommodation - Back and side wire: #14 AWG min. - #12 AWG max. solid and stranded copper wire only
- push wire: #14 AWG solid copper wire only

General

Catalog Number	RSD415W
EU RoHS Indicator	Yes
Specifications	• Base and body - PVC • Contacts - Copper alloy



UPC

- Mounting strap - Galvanized steel
- Rocker - Polycarbonate
- Terminal screws - Steel
- Terminals - Brass

883778101441

Certifications And Compliance

Industry Standard(s)	• CSA Certified • UL Listed E3896
----------------------	---

Logistics

Carton Quantity	10
Pallet Quantity	4500

Product Assets

[Catalog Page - WDK Z-3 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Installation Manuals - WIRING_PD2444_INSTALLINST](#)
[Literature - Residential Catalog](#)
[Literature - Residential Product Guide](#)
[Sales Drawings - WDK_RSD415_DRAWING_PDF](#)
[Specifications - RSD415W](#)
[Specifications - RSD415W Specification Sheet French](#)
[Specifications - WIRING_RSD415W_spec](#)
[Warranty - tradeSELECT™ and netSELECT®](#)
[Video - Tradeselect Devices](#)