

Flexible Steel Conduit

UL Listed Coil



Features

- Hot dipped galvanized zinc coating
- Corrosion and crush resistant
- Flexibility for simplified positioning
- Smooth interior for easy wire pull-through
- Easy installation to follow contours

Applications

- Voice, data, communications and video cables
- Motor feeder, branch and control circuit conductors and cables
- Remote-control, signaling and power limited circuit conductors and cables; Class 1-3
- Cables of power-limited or non-power limited fire alarm circuits, fire alarm system conductors
- Environmental air-handling spaces
- Elevators, escalators, and hoistways
- Concealed or exposed installations
- Metal raceway for wires and cables
- Grounding conductor for lengths up to 6 feet



Standard Material

- Galvanized steel

Standard Finish

- Hot dip galvanized zinc coating

Catalog Number	UPC	Size	Feet Coil	Ship Case	Weight/ Case	Thickness	Inside Diameter Min.	Inside Diameter Max.	Outside Diameter Min.	Outside Diameter Max.
5200C100UL	87291	3/8"	100'	100	23	.64	.393	.393	.56	.61
5200UL	87292	3/8"	250'	250	59	.64	.393	.393	.56	.61
5201UL	87293	1/2"	100'	100	29	.64	.625	.645	.86	.92
5202UL	87294	3/4"	100'	100	37	.64	.812	.835	1.045	1.105
5203UL	87295	1"	50'	50	31	.76	1	1.04	1.30	1.38
5204UL	87297	1-1/4"	50'	50	34	.76	1.25	1.30	1.55	1.63
5205UL	87298	1-1/2"	25'	25	19	.76	1.50	1.575	1.85	1.95
5206UL	87300	2"	25'	25	22	.76	2	2.08	2.35	2.454
5207UL	87301	2-1/2"	25'	25	44	1.05	2.50	2.70	2.86	3.06
5208UL	87302	3"	25'	25	51	1.05	3	3.20	3.36	3.56
5209UL	87303	3-1/2"	25'	25	61	1.05	3.50	3.50	3.86	4.60
5210UL	87304	4"	25'	25	72	1.05	4	4	4.36	4.56