

Specifications



Eaton AH7810GD

Eaton manual motor controller, #14-10 AWG, 30A, Wall, 600V, Front wired screw and clamp, Maintained contact, Gray, NEMA 1, Enclosure: SS, Three-pole, Single-gang, Two-position, Three-phase, Toggle, Copper-alloy terminal, Single-throw

General specifications

PRODUCT NAME	Eaton manual motor controller
CATALOG NUMBER	AH7810GD
UPC	040893598604
PRODUCT LENGTH/DEPTH	4.75 in
PRODUCT HEIGHT	3.25 in
PRODUCT WIDTH	3 in
PRODUCT WEIGHT	1.6 lb
COMPLIANCES	NAFTA RoHS Compliant
CERTIFICATIONS	cULus Listed
PRODUCT TYPE	Manual motor controller

Product specifications

NEMA RATING	1
ENCLOSURE	NEMA 1
SPECIAL FEATURES	With NEMA 1 enclosure
TYPE	Manual motor controller
AMPERAGE RATING	30A
VOLTAGE RATING	600 V
NUMBER OF POLES	Three-pole
PHASE	Three-phase
ENCLOSURE MATERIAL	Stainless steel
APPLICATION	Industrial
DEVICE GRADE	Industrial
WIRING METHOD	Front wired screw and clamp
CONTACT TYPE	Maintained
SWITCH TYPE	Toggle switch
MOUNTING METHOD	Wall
CLOSURE TYPE	Maintained
NUMBER OF GANGS	1
NUMBER OF POSITIONS	2
ALLOWABLE WIRE SIZE	#14-10 AWG
OPERATING TEMPERATURE	-20 to 65 °C
MATERIAL	Glass-filled nylon
TERMINATION STYLE	Front screw and clamp
THROW	Single-throw
TERMINALS	Copper-alloy, brass screw
COLOR	Gray

Resources

CATALOGS	Arrow Hart Buyers Guide Section E
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - AH7810GD

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

