



Representative Image

Catalog No. M051C010

Description: 70A SURFACE MTRD 50/20GFCI

UPC No 784567202748

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

| | |
|----------|-----------------|
| Category | Temporary Power |
|----------|-----------------|

Specifications

| | |
|--------------------------------|-----------------------|
| Mounting | Surface |
| Heads | 1 |
| Metering | Ring-Type |
| Receptacles | 10-50R 5-20WR2GFCI |
| Feed | Overhead |
| AIC | 10,000 |
| Amps | 70.0 A |
| Cabinet Size | 9 X 30 |
| Circuit Protection | Yes |
| Hub Provision | Yes |
| Installed Breaker | CB250 CB120 |
| Load Center | LC33N1 |
| Loop Feed | No |
| Phase | 1 |
| Suitable for Service Equipment | No |
| Unit Weight | 25.0 lb |
| Volts | 120/240 |

Classifications

| | |
|------------------|-----------|
| Standard Package | 1 |
| Stock Class Code | Non Stock |

Approvals

| | |
|---------------|--------|
| Certification | Non-UL |
|---------------|--------|

