

## GSTUD38HY Structural Steel Ground Stud

By Burndy

Catalog # [GSTUD38HY](#)

Structural Steel Grounding Connector



### Features

- May be welded to steel surfaces quickly and easily
- No disk grinding needed
- Knurled surface for better gripping
- Copper plated
- May be installed during adverse weather conditions

### Application

For Compression Connectors And Mechanical Connectors

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No
Certification - UL Listed Direct Burial	No

### Conductor

Conductor - Rod Size	3/8 in
Conductor - Copper Str Size	3 AWG
Conductor - Rod Size Range	3/8 in
Conductor - Copper Str Size Range	3 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• Rod-Size</li> <li>• CU C Str-Size</li> </ul>

### Dimensions

Dimension - L Length Overall mm	148 mm
Dimension - Ground Rod Size	3/8 in
Dimension - Height mm	0 mm
Dimension - B Length fraction	16/41 in
Dimension - B Length inch	0.39 in
Physical Attribute - Tongue Angle	45 Degree
Dimension - Length Overall inch	5.81 in
Dimension - D inch	1.25 in

### General

Trade Name	VERSITAIL™
Sub Brand	HYGROUND, VERSITAIL
Plated	Y
Type	GSTUD-HY
UPC 12 Digit	781810220887
UPC 14 Digit GTIN	00781810220887
Material	Steel
Plating Type	Nickel
UPC	781810220887

### Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	3920

### Product Assets

[Catalog \[English\]](#)