

Specifications



Photo is representative



Eaton DSD922

Eaton Crouse-Hinds series DSD front operated pushbutton cover and device sub-assembly, 10A, Green/red, Feraloy iron alloy, 2 circuits start-stop, 2 buttons, Factory sealed, 600 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series DSD front operated pushbutton cover and device sub-assembly
CATALOG NUMBER	DSD922
UPC	782274776279
PRODUCT LENGTH/DEPTH	5.3 in
PRODUCT HEIGHT	6.7 in
PRODUCT WIDTH	4.7 in
PRODUCT WEIGHT	3.9 lb

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2 Class II, Division 1 Class II, Division 2 Class III
NEMA RATING	3 7 9

Resources

CATALOGS	DSD and DSDX Cover and Device Sub-assemblies catalog page
CERTIFICATION REPORTS	DSD Explosionproof Cover and Device Sub-assemblies Canadian certification DSD Explosionproof Cover and Device Sub-assemblies UL certification
INSTALLATION INSTRUCTIONS	IF 1424 - DSD, GFS, CPS and ENR Series Replacement Covers IF 1929 - Toggle Operator for EDS, EDSX, EFD, DSD and DSDX Series IF 899 - EDSX, EDS, EFS, DSDX and DSD Control Stations
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DSD922

Product specifications

VOLTAGE RATING	600 Vac
NUMBER OF COVER BUTTONS	2
NORMAL POSITION	2 circuits start-stop
AMPERAGE RATING	10A
COLOR	Green/red
MATERIAL	Feraloy iron alloy
SPECIAL FEATURES	Factory sealed

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

