



**SKU:** PTT-2R-350-Z

**UPC:** 0783669750201

**Features & Benefits:**

**Description:** Aluminum Pole Type Overhead Transformer Lug, Dual Rated, Conductor Range 350-10, 2 Ports, Right Handed

## Specs

### Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1
Number of Ports / Wireways	2

### Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	1.25
Height BX (IN)	2.25
Height (mm)	31.75
Length (IN)	3.018
Length (mm)	76.6572
Weight (LB)	0.008
Weight BX (LB)	0.9159
Width (IN)	4
Width BX (IN)	5
Width (mm)	101.6

### Material and Finish

Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	11/16



### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 2
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366975020

### Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
-------------------	--

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 10 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 10 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol

### Color

Color	Silver
-------	--------