

We MERSEN USA EP Corp.
374 Merrimac Street Newburyport, MA 01950 USA

Certify that products with the registered trade mark Mersen Ferraz Shawmut

Product type High-Speed and Semiconductor protection fuses
Round Body High-Speed Fuse-Links AC Protection

Model Series Line Amp-Trap® A70P 700VAC 650VDC

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:

RoHS directive N° 2011/65/UE

RoHS directive N° 2015/863

https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided below is based on data obtained through ongoing due diligence with our suppliers. In some cases, the information may not yet represent full coverage of our supply chain. Mersen reserves the right to update or amend this declaration as additional data becomes available, or verification processes are completed.

This declaration is not an EU or UKCA declaration of conformity, Mersen USA EP Corp. is providing RoHS conformity to all product ranges even if they are out of the scope of the directive with the same level of compliance on substances restrictions and corresponding exemptions.

Date / Location : 19.05.2026 / Newburyport

Name : Tim KAPPEN

Position / Signature :

Sr. Manager Quality
For the president and by delegation



COMP-016693

Catalog number list

Item number	ROHS exemption
A70P70-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P80-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P90-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P100-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P1000-4	
A70P900-4	
A70P1000-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P1000-4TI	
A70P100-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P80-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P80-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P100-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P70-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P125-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P150-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P175-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P200-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P2000-4	
A70P1400-4	
A70P1600-4	
A70P1500-4	
A70P1200-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P1600-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P2000-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P1600-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P125-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P200-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P150-4TA	6(c) - Copper alloy containing up to 4% lead by weight

A70P125-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P200-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P150-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P250-4	
A70P300-4	
A70P350-4	
A70P400-4	
A70P225-4	
A70P300-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P350-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P400-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P225-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P250-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P400-4TI	
A70P250-4TI	
A70P35-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P40-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P50-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P60-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P450-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P500-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P600-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P600-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P500-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P600-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P40-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P60-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P60-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P35-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P40-4TI	6(c) - Copper alloy containing up to 4% lead by weight

A70P700-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P800-4	6(c) - Copper alloy containing up to 4% lead by weight
A70P800-4TA	6(c) - Copper alloy containing up to 4% lead by weight
A70P700-4TI	6(c) - Copper alloy containing up to 4% lead by weight
A70P800-4TI	6(c) - Copper alloy containing up to 4% lead by weight