

Locking Devices, Twist-Lock®, Safety-Shroud® Receptacle, 30A, 250V AC, 2 Pole, 3 Wire Grounding, NEMA L6-30R, RPT angle housing, One Gang, Gray

By Hubbell Wiring Device-Kellems
Catalog # [HBL2620AR](#)



Locking Devices, Twist-Lock®, Safety-Shroud® Receptacle, 30A, 250V AC, 2 Pole, 3 Wire Grounding, NEMA L6-30R, RPT angle housing, One Gang, Gray

Features

- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
- Catalog number and color coded voltage rating are visible even when in use
- Engineered thermoplastic housing is impact and corrosion resistant, making it suitable for heavy-duty industrial environments

Performance

- Electrical-Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498
- Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17
- Environmental - Moisture Resistance - IP20 Suitability
- Environmental - Operating Temperatures - Maximum Continuous 75°C
- Minimum -40°C (w/o impact)

General

Catalog Number	HBL2620AR
EU RoHS Indicator	Yes
Horsepower - Maximum	2
Item Type	30A Safety-Shroud® Receptacle
Listings	<ul style="list-style-type: none">• UL 498• Fed.Spec. W-C-596• CSA C22.2 No.42
Material	Valox™
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Number of Gang(s)	1-Gang

Operating Temperature

Maximum continuous 75°C and minimum -40°C without Impact

Specifications

- Body Contact Carrier - Natural (white) nylon
- Body Holding Screws - Steel, zinc plated
- Contacts - Brass
- Housing / Flange - Gray RPT
- Mounting Plate - Steel, zinc plated
- Terminal Retainer - Clear polycarbonate

UPC

783585234328

Dimensions

Dimensions	4.77 in x 2.85 in x 3.14 in
Display Size	Standard Sized Product
Height	3.14 in
Length	4.77 in
Weight	0.65 lb
Width	2.85 in

Electrical Ratings

Amperage Rating	30 A
Connectivity	Back Wired Screw Terminals
Current / Amperage Rating	30 A
Current Rating	30 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	250 VAC

Conductor Related

Number Of Wires	3-Wire Grounding
Wire Size	#16 AWG to #8 AWG

Certifications And Compliance

Industry Standard(s) • Certified to CSA C22.2 No.42
• Fed.Spec. W-C-596
• Listed to UL 498

Nema Rating L6-30R

Logistics

Carton Quantity 10

Product Assets

[Catalog Page - WDK B-29 Catalog Page](#)

[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - HBL2620AR AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD1291_INSTALLINST](#)
[Sales Drawings - WDK_HBL2620AR_DRAWING_PDF](#)
[Specifications - HBL2620AR Specification Sheet French](#)
[Specifications - Wiring HBL2620AR Specification Sheet](#)
[Specifications - HBL2620AR Specification Sheet](#)
[Warranty - Industrial & Commercial Products](#)
[Video - Insulgrip Twist-Lock and Straight Blade Devices](#)
[Video - Insulgrip Twist-Lock and Straight Blade Devices](#)
[Video - Twist-Lock Devices](#)



A Hubbell brand