



<p>Note: - Drawings Not To Scale - Drawings Subject to Change Without Notice - Dimensions are inches next to [Millimeters]</p>

Part No.:

PLL34060



Schneider Electric United States
 North American Division
 Boston One Campus
 800 Federal Street
 Andover, MA 01810, USA
 Phone: +1 8773425173
 Email: CCC@us.schneider-electric.com

Technical Information:

General Application: Provides overload and short circuit protection
 For Use With: Panelboards and Switchboards
 Approvals: UL Listed - CSA Certified - IEC Rated
 Mounting Type: Unit Mount
 Terminal Type: Lugs (ON and OFF ends)
 Wire Size: #3/0-500 AWG/kcmil(Al/Cu)
 Weight: 32 Pounds
 Depth: 8.07 Inches
 Height: 12.86 Inches
 Width: 8.27 Inches

Description:
 Number of Poles: 3-Pole
 Sensor Rating: 600A
 Voltage Rating: 480VAC
 Interrupting Rating: 125kA at 240VAC - 100kA at 480VAC - 25kA at 600VAC
 Circuit Breaker Rating: 80% Rated
 Electronic Trip Unit: Basic (ET1.0I)
 Trip Function: Installed Rating Plug: Fixed Long-Time Adjustable Instantaneous Trip
 Rating Plug Range:

Specification:

PowerPact P-frame Electronic Trip Circuit Breaker
 3-Pole
 600A
 480VAC
 125kA at 240VAC - 100kA at 480VAC - 25kA at 600VAC
 80% Rated
 Basic (ET1.0I)
 Fixed Long-Time Adjustable Instantaneous Trip