



Pass and Seymour

**15A 120V/125V Combination Single-Pole Toggle Switch and Single Receptacle, Light Almond**

Part No. 691LA

Our standard Pass and Seymour combination switches allow you to add lights to any room in your home without having to add or replace wall boxes.



## Features & Benefits

Easily accessible break-off separate or common feed.

One-piece heat-treated triple-wipe brass power contacts.

Two devices fit into the space of one.

Grounding combination devices meet NEC Requirements.

Tamper-resistant version features dual mechanical shutter system to help prevent insertion of foreign objects.

## Specifications

### General Info

|                    |                             |                     |                         |
|--------------------|-----------------------------|---------------------|-------------------------|
| Product Line       | Pass & Seymour              | Color               | Light Almond            |
| Finish             | Satin                       | UPC Number          | 785007691054            |
| Country Of Origin  | Mexico                      | Features            | Combination             |
| Switch Type        | Toggle                      | Number of Switches  | 1                       |
| Application Sector | Hospitality, Residential    | Wall Plate Included | No                      |
| Standard           | UL20, UL498                 | Warranty Type       | 1-Year Limited Warranty |
| Type               | Combination, Outlet, Switch |                     |                         |

### Dimensions

|                   |         |                  |         |
|-------------------|---------|------------------|---------|
| Product Width US  | 1.32 in | Product Depth US | 0.94 in |
| Product Height US | 4.06 in |                  |         |

### **Listing Agencies / 3rd Party Agencies**

|                      |        |              |     |
|----------------------|--------|--------------|-----|
| cULus Listing Number | 140597 | cULus Listed | Yes |
|----------------------|--------|--------------|-----|

### **Technical Information**

|                          |                       |                        |  |
|--------------------------|-----------------------|------------------------|--|
| Load Rating              | 15 A @ 120/125 VAC    | Seismic Tested         | No   |
| Contact Configuration    | N-0                   | Operating Cycles       | 30000  |
| Connection Location      | Side Only             | Terminal Accommodation | #14 AWG - #12 AWG  |
| Number of Gangs          | 1                     | Throw Type             | Single Throw   |
| Amperage                 | 15 A                  | Number of Poles        | Single Pole  |
| Requires Neutral Wire    | Yes                   | Indoor/Outdoor         | Indoor   |
| Mounting Type            | Wall Box              | Wire Connection Type   | Screw Terminals  |
| Voltage                  | 120 VAC, 125 VAC      | Load Type              | CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon |
| Environmental Conditions | Flammability: UL94 V2 |                        |  |