

Specifications

Photo is representative

Eaton CPP4752

Eaton Crouse-Hinds series Arktite CPP plug, 7A/30A, 0.375-0.875" cable diameter, Three-wire, four-pole, Brass contacts, 60 Hz, Style 2, 1 HP/3 HP, Copper-free alum, Factory sealed, Delayed action circuit breaking, 125-250 Vac/480 Vac

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series Arktite CPP plug
CATALOG NUMBER	CPP4752
UPC	782274175904
PRODUCT LENGTH/DEPTH	6.38 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	2.5 in
PRODUCT WEIGHT	1.2 lb

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2

Product specifications

GROUNDING STYLE	Style 2
AMPERAGE RATING	7A/30A
CONFIGURATION	Three-wire, four-pole
CABLE DIAMETER	0.375-0.875 in
VOLTAGE RATING	125-250 Vac/480 Vac
HORSEPOWER	1 hp/3 hp
FREQUENCY RATING	60 Hz
MATERIAL	Copper-free aluminum
CONTACT MATERIAL	Brass
SPECIAL FEATURES	Factory sealed
TYPE	Delayed action circuit breaking

Resources

CATALOGS	Arktite CPS and CPP Explosionproof Receptacles and Plugs catalog page
CERTIFICATION REPORTS	Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors Canadian certification Arktite CPS, CPP, CPR Explosionproof Receptacles, Plugs and Connectors UL certification
INSTALLATION INSTRUCTIONS	IF 285 - CPP Plugs
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CPP4752

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

