

Product data sheet

Characteristics

QO220PL

Mini circuit breaker, QO, 20A, 2 pole,
120/240VAC, 10kA, Powerlink, plug in mount



Main

| | |
|-----------------------|-----------------|
| Product | Circuit breaker |
| Range | QO |
| Current Rating | 20 A |
| Voltage Rating | 120/240 V AC |
| Mounting Type | Plug-in |
| Number of Poles | 2P |
| Circuit Breaker Type | Standard |
| Ratings | HACR rated |
| Electrical Connection | Box lugs |

Complementary

| | |
|------------------------|---|
| Interrupt Rating | 10 kA 120/240 V AC 50/60 Hz |
| Number of Panel Spaces | 2 |
| Provided Equipment | 18 in (457.20 mm) lead |
| Wire Size | AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper |
| Tightening Torque | 35.40 lbf.in (4 N.m) |
| Height | 4.57 in (116 mm) |
| Width | 1.50 in (38 mm) |
| Depth | 2.91 in (74 mm) |
| Net Weight | 0.84 lb(US) (0.381 kg) |

Environment

| | |
|----------------|----------------------|
| Certifications | UL Listed[RETURN]CSA |
| Ambient Rating | 104 °F (40 °C) |

Ordering and shipping details

| | |
|-------------------|----------------------------------|
| Category | 09650-POWERLINK QO(B)PL BREAKERS |
| Discount Schedule | DE8A |
| GTIN | 785901095736 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.10 in (5.334 cm) |
| Package 1 Width | 3.50 in (8.89 cm) |
| Package 1 Length | 5.30 in (13.462 cm) |
| Package 1 Weight | 13.44 oz (381.018 g) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|-----------------------------|--|
| California proposition 65 | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|