

EMT Conduit Bodies with Cover and Gasket

Set Screw C Type

Features

- Set screw C type with cover and gasket
- Suitable for use in concrete

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast
- Steel screws
- Cover - Stamped steel
- Gasket - Neoprene rubber

Standard Finish

- Powder coat



UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
EC1CG	20411	1/2"	1	6 AWG	10	100	31	4.72	1.37	1.33
EC2CG	20421	3/4"	2	6 AWG	10	50	21	5.57	1.625	1.54
EC3CG	20431	1"	3	6 AWG	5	25	17	6.46	1.90	1.74
EC4CG	20441	1-1/4"	3	2 AWG	2	10	14	8.528	2.77	2.49
EC5CG	20451	1-1/2"	3	2 AWG	2	10	15	8.528	2.77	2.49
EC6CG	20465	2"	3	2/0 AWG	1	5	10	10.831	3.335	3.10
EC7CG	20466	2-1/2"	3	4/0 AWG	---	1	4	13	4.063	5.709
EC8CG	20467	3"	3	250 MCM	---	1	5	12.50	4.682	5.506
EC9CG	20468	3-1/2"	3	350 MCM	---	1	8	15.50	5.452	6.171
EC10CG	20469	4"	4	350 MCM	---	1	8	15.50	5.452	6.171