

# Product data sheet

## Characteristics

# QBL32000S22

Automatic switch, PowerPacT Q, 225A, 3 pole, 480VAC, lugs, magnetic



### Main

Product or Component Type	Automatic switch
Range of Product	PowerPact Q
Trip unit technology	Magnetic
Circuit breaker type	Q-Frame

### Complementary

Line Rated Current	225 A
[Ue] rated operational voltage	240 V AC
Mounting Mode	Unit mount
Poles description	3P
Short-circuit withstand	10 kA 240 V UL 489
Breaking capacity code	B
Electrical connection	Lugs line Lugs load
AWG gauge	X AWG 4...300 kcmil ( aluminium/copper )
Magnetic tripping current	4500 A
Height	16.24 in (412.50 mm)
Width	16.54 in (420.12 mm)
Depth	14.49 in (368.05 mm)
Tightening torque	247.82 lbf.in (28 N.m) 0.04...0.23 in <sup>2</sup> (25...150 mm <sup>2</sup> ) (AWG 4...300 kcmil)

### Environment

Product Certifications	CSA UL Listed IEC
------------------------	-------------------------

### Ordering and shipping details

Category	00023-QO,Q2L 3P ENCL & BREAKERS
Discount Schedule	DE2
GTIN	785901417859
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.10 in (15.494 cm)
Package 1 Width	6.10 in (15.494 cm)
Package 1 Length	9.80 in (24.892 cm)
Package 1 Weight	4.73 lb(US) (2.145 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------