

Specifications



Photo is representative

Eaton EIDCF3200

Eaton Crouse-Hinds series EID disconnect switch, 200A, With switch, Fused, 40 HP/60 HP/125 HP/150 HP, Copper-free aluminum, 240-600 Vac/250 Vdc

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series EID disconnect switch
CATALOG NUMBER	EIDCF3200
UPC	662276482036
PRODUCT LENGTH/DEPTH	17.44 in
PRODUCT HEIGHT	29.44 in
PRODUCT WIDTH	13.19 in
PRODUCT WEIGHT	167 lb

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Zone 1 Class I, Division 2 Class I, Zone 2 Class II, Division 1 Class III
NEMA RATING	3 3R 4 7 9

Resources

3D CAD DRAWING PACKAGE	Eaton Crouse-Hinds EIDCF3200 3D drawing
3D MODELS	SP3D Design Package - EID Explosionproof Compact Disconnect Switches
BROCHURES	EID Series Explosionproof, Compact Disconnect Switches Brochure
CATALOGS	EID Series Explosionproof, Compact Disconnect Switches catalog page
CERTIFICATION REPORTS	EID Explosionproof, Compact Disconnect Switches Canadian certification EID Explosionproof, Compact Disconnect Switches UL certification
INSTALLATION INSTRUCTIONS	IF 1697 - EID 200A and 400A Disconnect IF 1532 - EID Disconnect Assembly IF 1696 - EID Fusible Disconnect Switch
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - EIDCF3200 EID Explosionproof Disconnect Switches

Product specifications

ENCLOSURE TYPE	With switch
FUSING	Fused
AMPERAGE RATING	200A
HORSEPOWER	40 hp/60 hp/125 hp/150 hp
MATERIAL	Copper-free aluminum

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

