

# Eaton DFLMY250/MT 76 S828

Catalog Number: DFLMY250/MT 76 S828

Eaton Crouse-Hinds series Pauluhn DFL floodlight, 60 Hz, HID-Pulse start metal halide lamp, Heat and impact resistant glass lens, Die cast aluminum, Yoke mount, 7x6 optical distribution, Multi-tap, 250W

## General specifications

Product Name	Catalog Number
Eaton Crouse-Hinds series Pauluhn DFL DFLMY250/MT 76 S828 floodlight	
UPC	662276240810
Product Length/Depth	Product Height
19.1 in	23.6 in
Product Width	Product Weight
6.8 in	42 lb

## Certifications and compliances

Area classification	
Hazardous/Classified Locations	
Standards type	
NEC/CEC	
NEC hazardous rating	
Class I, Zone 2	
Class I, Division 2	
Class II, Division 1	
NEMA Rating	
4X	
Ingress protection (IP) ratings	
IP66	

## Product specifications

Lamp type	
HID-Pulse start metal halide	
Wattage	
250W	
Mounting Method	
Yoke	
Optical distribution	
7x6	
Material	
Die cast aluminum	
Lens material	
Heat and impact resistant glass	
Voltage rating	
Multi-tap	
Frequency rating	
60 Hz	

## Resources

### Catalogs

[Crouse-Hinds Pauluhn DFL Hazardous Area HID Floodlights catalog page](#)

### Installation instructions

[IF 1620 - Pauluhn DFL Floodlight](#)

### Specifications and datasheets

[Eaton Specification Sheet - DFLMY250/MT 76 S828](#)

Eaton Corporation plc

Eaton House

30 Pembroke Road

Dublin 4, Ireland

[Eaton.com](#)

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.