




PH MULTI-PURPOSE PURLIN CLAMP, 1/4" ROD, 1/4" MAX FLANGE

CATALOG NUMBER

PH4



CERTIFICATIONS



FEATURES

Attaches to bottom of purlins and beams to support threaded rod

PRODUCT ATTRIBUTES


Material: Steel
Finish: Electrogalvanized
Rod Size: 1/4"
Flange Thickness: 1/4" Max
B: 3/4" Min
Torque: 30 in lb
Static Load 1: 200 lb
Static Load 2: 160 lb
Nut Included: No

ADDITIONAL PRODUCT DETAILS

A jam nut is required for fire protection applications.

Refer to Static Load 1 when attaching to C and Z purlins. Refer to Static Load 2 when attaching to a flat flange.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500