



SIEMENS LOW VOLTAGE ES SERIES LOAD CENTER. FACTORY INSTALLED MAIN BREAKER WITH 42 1-INCH SPACES ALLOWING MAX 42 CIRCUITS. 3-PHASE 4-WIRE SYSTEM RATED 120/240V OR 120/208V (225A) 10KA INTERRUPT. SPECIAL FEATURES: ALUMINUM BUS, GRAY TRIM, NEMA TYPE1 ENCLOSURE FOR INDOOR USE.

| General technical data                                       |             |
|--------------------------------------------------------------|-------------|
| configuration of the busbars                                 | 225 A       |
| fastening method                                             | Combination |
| product function note                                        |             |
| phase number                                                 | 3           |
| suitability for operation                                    | Residential |
| Electricity                                                  |             |
| ampacity                                                     | 225 A       |
| ampacity minimum                                             | 225 A       |
| voltage between phase and Ground (GND) rated value           | 120 V       |
| voltage between phase and phase rated value                  | 240 V       |
| Breaking Capacity                                            |             |
| switching capacity current according to EN 60898 rated value | 22000 A     |
| Model                                                        |             |
| product brand name                                           | Siemens     |
| Mechanical Design                                            |             |
| number of modular width units for installation width         | 42          |

last modified:

10/22/2025 

