

Product data sheet

Specifications



Main breaker, QO, 125A, 2 pole, 120/240VAC, 22kA, bolt on

QOM125VH

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	125 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	Primary main breaker
Electrical Connection	Lugs
Frame Size	QOM1

Complementary

Interrupt Rating	22 kA 120/240 V AC 22 kA 120 V AC
Wire Size	12 AWG...2/0 AWG copper or aluminium
Tightening Torque	53.1 lbf.in (6 N.m) 0.006...0.1 in ² (4...65 mm ²) (12 AWG...2/0 AWG)
Height	5.08 in (129 mm)
Width	5 in (127 mm)
Depth	3.5 in (88 mm)
Product Weight	1.261 lb(US) (0.572 kg)
Load Center Type	Main breaker
Number of Phases	1 phase
For Use With	QO load center Homeline load center
Breaker compatibility	Miniature circuit-breaker QO Miniature circuit-breaker Homeline

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE3A00100
----------	--------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	DE3A
GTIN	785901004042
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.300 in (10.922 cm)
Package 1 Width	4.200 in (10.668 cm)
Package 1 Length	5.300 in (13.462 cm)
Package weight(Lbs)	21.920 oz (621.421 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	251 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	248 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	770cc9ea-53d2-4d3d-a57a-062b35abd847
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	0
Circularity Profile	No need of specific recycling operations
Take-back	No

Image of product / Alternate images

Alternative



