

# Product data sheet

Specifications

SQUARE D



Contactor, Type L, multipole lighting, replacement coil, 110/120VAC 50/60Hz, 8903L 2 to 6 poles, 8903LX 2 to 4 poles

9998L44

**Product availability:** Non-Stock - Not normally stocked in distribution facility

## Main

Product or Component Type	Coil
Accessory / separate part destination	Class 8903 contactor

## Complementary

[Ue] rated operational voltage	120 V AC 60 Hz 110 V AC 50 Hz
inrush power in VA	150 VA 140 VA
Average consumption	30 VA
Height	2.4 in (60.5 mm)
Width	2.1 in (53.6 mm)
Depth	1.5 in (37.1 mm)

## Ordering and shipping details

Category	US1CP1021756
Discount Schedule	CP10
GTIN	785901081210
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.100 in (5.334 cm)
Package 1 Width	2.800 in (7.112 cm)
Package 1 Length	3.300 in (8.382 cm)
Package weight(Lbs)	5.600 oz (158.757 g)

## Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

## Use Again

### Repack and remanufacture

Take-back	No
-----------	----