



SKU: CLNS-2-12

UPC: 0783669633108

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 2, 1 Hole, 1/2in Bolt Size, Long Barrel, No Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Catalog Number	ILD-33
ILSCOs Die Index Number	I-33
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	No
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.125
Barrel Length (mm)	28.575
Dimension G (IN)	0.546
Dimension G (mm)	13.8684
Height (IN)	0.452
Height BX (IN)	2.25
Height (mm)	11.4808
Inside Diameter (IN)	0.312
Inside Diameter (mm)	7.9248
Length (IN)	2.661
Length (mm)	67.5894
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.422
Outside Diameter (mm)	10.7188
Strip Length (mm)	30.1498
Tang Length (IN)	1.25
Tang Length (mm)	31.75
Tang Thickness (IN)	0.109
Tang Thickness (mm)	2.7686

Tang Width (IN)	0.744
Tang Width (mm)	18.8976
Weight (LB)	0.0517678965402915
Weight BX (LB)	2.1117
Width (IN)	0.744
Width BX (IN)	5
Width (mm)	18.8976

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	2 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	2 Str - 6 Str
Flex Conductor Range	NA

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963310

Bolt and Screw Sizes

Mounting Bolt/Stud Size	1/2
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature



Temperature Rating

90°C

Color

Color

Silver

Color Code

Brown

Voltage

Voltage Rating

35 kV