

Circuit Guard® Extra Heavy Duty Hard Wired GFCI with Manual Set, 30A, 3Ø 250V AC, Black

By Hubbell Wiring Device-Kellems

Catalog # [GFHW530](#)



Power Protection Products, Hard Wired GFCI,
Industrial/Commercial, No Output, 30A 3-Phase 250V AC, 4-6
mA Trip Level, Black.

Features

- Electromagnetic Latching Mechanism
- Trips if ground and neutral touch at load side
- Red blinking light plus optional audible alarm
- Open neutral protection Trips upon loss of neutral

Application

- Wire Into Circuit

Performance

- Electrical - Dielectric Withstand - 1500 VRMS across contact, 4000 VRMS between conductors & enclosure
- Electrical - Operating Voltage Range - 85% to 110%
- Electrical - Rated Voltage - 120V AC, 240V AC & 120/240V, 3Ø 250V AC, 3Ø 120/208V AC
- Electrical - Surge Withstand - 6000V impulse, 0.5 ms rise time 100kHz ringing frequency
- Environmental - Construction - Industrial grade design
- Environmental - Housing Rating - UL Type 4X
- Environmental - Leakage Current - At 93% Humidity leakage current is zero
- Environmental - Operating Temperature - -35°C to 66°C, -30°F to 150°F.
- Environmental - Type - Class A GFCI

General

Catalog Number	GFHW530
Color	Black
Construction	Fabricated
EU RoHS Indicator	No
Item Type	Industrial Grade
Material - Insulation	Thermoplastic
OEM Brand Name	Hubbell Wiring Device-Kellems
Series	Extra Heavy Duty
Specifications	<ul style="list-style-type: none"> • Response Time - .025 sec. Max • Switch Interface - Double Insulated • Trip Level - 4 to 6 mA

Style	Unit Color - Gray with black cover
Temperature Rating	-35 Degrees C to 66 Degrees C (-30 Degrees F to 150 Degrees F)
Type	Hard Wired
UPC	783585521060

Dimensions

Weight	2.2 lb
--------	--------

Electrical Ratings

Amperage Rating	30 A
Connectivity	Hard Wired
Current / Amperage Rating	30 A
Current Rating	30 A
Voltage Rating	3 Phase 250 VAC
Voltage Rating Description	3 Phase 250 VAC

Conductor Related

Conductor Size	#10 AWG
Conductor Type	Copper
Number of Conductors	4
Strands	Multi

Certifications And Compliance

Industry Standard(s)	cCSA
----------------------	------

Logistics

Carton Quantity	5
-----------------	---

Product Assets

Catalog Page - WDK K-18 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - GFHW530 AutoCAD Drawing

[Installation Manuals - WIRING_PD1978_INSTALLINST](#)

[Literature - Safety Product Guide](#)

[Literature - 20A & 30A GFCI Protected Cord Drops](#)

[Literature - PULP & PAPER SOLUTIONS](#)

[Literature - Pulp & Paper Solutions](#)

[Sales Drawings - WDK_GFHW530_DRAWING_PDF](#)

[Specifications - GFHW530](#)

[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
WDK-GFHW530-SPEC-EN | REV 1/2025