

Flexible Liquidtight Conduit

Metallic - Coil

Features

- Crush and corrosion resistant steel core for lasting mechanical protection
- EF PVC jacket is oil and sunlight resistant
- Smooth interior for easy wire pull through

Applications

- For use in damp or wet locations, suitable for commercial and industrial use
- Non UL

Standard Material

- EF PVC jacketed steel core coil wrapped in clear plastic shrink wrap



Catalog Number	UPC	Size	Feet Coil	Ship Case	Weight/ Case	Outside Diameter		Inside Diameter	
						Min.	Max.	Min.	Max.
6100	80414	3/8"	100'	100	16	.689	.709	.484	.504
6101	80415	1/2"	100'	100	26	.819	.839	.622	.642
6102	80417	3/4"	100'	100	31	1.032	1.051	.815	.835
6103	80419	1"	100'	100	44	1.287	1.315	1.032	1.055
6104	80421	1-1/4"	50'	50	46	1.63	1.661	1.37	1.394
6105	80423	1-1/2"	50'	50	35	1.866	1.902	1.579	1.598
6106	80425	2"	25'	25	22	2.339	2.374	2.02	2.043
6106C50	86340	2"	50'	50	49	2.339	2.374	2.02	2.043
6107	80427	2-1/2"	25'	25	42	2.839	2.874	2.48	2.504
6108	80429	3"	25'	25	53	3.461	3.50	3.071	3.102
6109	80430	3-1/2"	25'	25	55	3.96	4	3.50	3.54
6110	80431	4"	25'	25	57	4.457	4.50	4	4.039