

SKU: T4A4-800N

UPC: 0783669912319

Features & Benefits:

Description: Aluminum Mechanical Lug, Conductor Range 800-300, 4 Ports, 4 Holes, 1/2in Bolt Size, Tin Plated, UL, CSA



Fig. 1



Fig. 2



Fig. 3



Fig. 4

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	4
Number of Mounting Holes	4
Number of Poles	1
Number of Ports / Wireways	4

Dimensions

Dimension G (IN)	0.625
Dimension G (mm)	15.875
Drive Size Main	1/2
Drive Type Main	Internal Hex
Height (IN)	1.813
Height BX (IN)	4.25
Length (IN)	5.97
Mounting Bolt/Stud Size (mm)	304.8
Mounting Hole Diameter (IN)	0.562
Mounting Hole Diameter (mm)	14.2748
Mounting Hole Spacing (IN)	1.75
Mounting Hole Spacing (mm)	44.45
Tang Length (IN)	3.625
Tang Length (mm)	92.075
Tang Thickness (IN)	0.5
Tang Thickness (mm)	12.7
Tang Width (IN)	6
Tang Width (mm)	152.4
Weight (LB)	3.523
Weight BX (LB)	3.8346
Width (IN)	6
Width BX (IN)	7.75

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum

Voltage

Voltage Rating

35 kV