

# Product data sheet

Specifications

SQUARE D



## Circuit breaker accessory, PowerPacT, shunt trip, 110VAC to 130VAC

S29386

Product availability: Stock - Normally stocked in distribution facility

### Main

Range of Product PowerPact

Circuit breaker type Standard

### Complementary

Tightening torque 12.4 lbf.in (1.4 N.m)

Width 1.28 in (32.51 mm)

Depth 1.24 in (31.50 mm)

Height 1.72 in (43.69 mm)

### Ordering and shipping details

Category US10DE201103

Discount Schedule 0DE2

GTIN 785901712282

Returnability Yes

Country of origin US

### Packing Units

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

### Contractual warranty

Warranty 18 months

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
REACH Regulation	<a href="#">REACH Declaration</a>
California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Use Again

### Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.