

Product data sheet

Characteristics

8903SQO11V02

Contactor, Type S, multipole lighting, mechanically held, 100A, 3 pole, 110/120 VAC 50/60 Hz coil, open style



Main

| | |
|---------|--------------------------------------|
| Product | Mechanically Held Lighting Contactor |
| Type | S |

Complementary

| | |
|-------------------------|----------------------------------|
| Control Circuit Voltage | 120 V AC 60 Hz 110 V AC 50 Hz |
| Current Rating | 100 A |
| Number of Poles | 3P |
| Control Units | No control units |
| Pilot Light | Without pilot light |
| Auxiliary Contacts | Without |
| Other Options | None |
| Electrical Connection | Lugs |
| Height | 7.24 in (184 mm) |
| Depth | 6.73 in (171 mm) |
| Width | 5.94 in (151 mm) |

Environment

| | |
|------------------------|--------------------------------------|
| Enclosure Type | Not rated (open device) surface none |
| Product Certifications | UL Listed CSA |

Ordering and shipping details

| | |
|-------------------|------------------------------|
| Category | 21324-8903 S (NOT S*C) MECH. |
| Discount Schedule | CP1 |
| GTIN | 785901102427 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 9.60 in (24.384 cm) |
| Package 1 Width | 13.70 in (34.798 cm) |
| Package 1 Length | 17.80 in (45.212 cm) |
| Package 1 Weight | 18.15 lb(US) (8.233 kg) |

Offer Sustainability

| | |
|---------------------------|--|
| California proposition 65 | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Not compliant |
| China RoHS Regulation |  China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|