Product data sheet

Specifications



Load center, Homeline, 1 phase, 20 spaces, 40 circuits, 100A convertible main breaker, PoN, NEMA1, Qwik-grip, value pack

HOM2040M100PQCVP

Product availability: Stock - Normally stocked in distribution facility

Main

Product Type	Load Center
Marketing Trade Name	Homeline
Load Center Type	PoN Convertible Mains (breaker)
Rated Current	100 A
Number of Spaces	20
Maximum Number of Single Pole Circuits	40
Enclosure Rating	NEMA 1 indoor enclosure
Cover Type	Combination flush/surface cover
Electrical Connection	Lugs
Provided Equipment	Circuit-breaker 2) 1P 20 A 120/240 V AC Circuit-breaker 1) 2P 100 A 120/240 V AC main supply ready assembled Circuit-breaker 1) 2P 30 A 120/240 V AC Load center 1) Qwik grip assembly kit 1)

Complementary

Max Short Circuit Current Rating	10 kA
Maximum Number of Tandem Breakers	20
Number of Phases	1 phase 3 wires
Voltage Rating	120/240 V AC
Wire Size	AWG 6...AWG 2/0 aluminium AWG 6...AWG 1 copper
Ground Bar	Grounding bar (ordered separately)
Enclosure Material	Welded galvannealed steel
Surface Finish	Baked enamel Gray
Box Number	6
Bus Rated Current	125.0 A
Height	17.9 in (455 mm)
Width	14.3 in (362 mm)
Depth	3.7 in (95 mm)

Environment

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)

Ordering and shipping details

Category	US1DE3C00185
Discount Schedule	DE3C
GTIN	785901639343
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.25 in (13.34 cm)
Package 1 Width	15.81 in (40.16 cm)
Package 1 Length	22.75 in (57.79 cm)
Package weight(Lbs)	22.639 lb(US) (10.269 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	35
Package 2 Height	40.0 in (101.6 cm)
Package 2 Width	42.008 in (106.7 cm)
Package 2 Length	48.0 in (121.9 cm)
Package 2 Weight	818.8 lb(US) (371.4 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**56 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**51 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**3 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0.1 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**1 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**89**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative

