

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART #	WIRE RANGE		REEL QTY.	COLOR (DIN)	MAX. WIRE INSUL. DIA.	WIRE CLASS	DIMENSIONS - in [mm]				CP-881 INSERTS	SCA-71202 2002 (CA10) DIE SET	UNI-M	** UNI-M (JM9D) INSERTER KIT/ *** UNI-M (JVD) FUNNEL KIT	
	AWG	[mm ²]					L	P	OD (REF.)	ID					
* FSD75-8-3K10	22-20	[0,50]	3000	WHITE	.09 [2,4]	B, K, M	.57 [14,5]	.31 [8]	.05 [1,4]	.04 [1,0]	WHITE INSERTS	SCA-71200 2005WE (CD10-1)	ALL ONE DIE SET	APM-K008701/ APM-K017697	
											GRAY INSERTS				
FSD76-8-3K8	18	[0,75]	3000	GRAY	.10 [2,6]	B, K, M	.57 [14,5]	.31 [8]	.06 [1,6]	.05 [1,2]				APM-K008175/ APM-K015949	
FSD77-8-3K2	-	[1,0]	3000	RED	.11 [2,8]	B, K, M	.57 [14,5]	.31 [8]	.07 [1,8]	.06 [1,4]	RED INSERTS	SCA-71200 2006WE (CD10-2)			
											BLACK INSERTS				APM-K006667/ APM-K017698
FSD78-8-2KD0	16	[1,5]	2500	BLACK	.13 [3,3]	B, K, M	.57 [14,5]	.31 [8]	.08 [2,1]	.07 [1,7]					
FSD80-8-KD6	14	[2,5]	1500	BLUE	.15 [3,9]	B, K, M	.57 [14,5]	.31 [8]	.10 [2,6]	.09 [2,2]	BLUE INSERTS	SCA-71200 2007WE (CD10-3)			APM-K008585/ APM-K017699

* UL LISTED WITH 20 AWG ONLY, UL486F SCOPE IS 20 – 1/0 AWG. WHITE IS DIN COLOR FOR 20 AWG [0,5]

** INSERTER KIT OPTIONAL. (MRSP1516JM9D)



*** VERTICAL FUNNEL KIT OPTIONAL. (APM-MRSP1516JVD/APM-MRSP1516-PAN)


NOTES:

1. USED FOR:
 - A. UL LISTED WITH STRANDED COPPER WIRE ONLY
 - B. 221°F [105°C] MAX. OPERATING TEMPERATURE
2. INSTALLATION TOOLS PANDUIT APPROVED:
 - A. CA10 APPLICATOR WITH CP-871 OR EQUIVALENT PRESS
 - B. CP-881 STRIP AND CRIMP UNIT
 - C. SCA-712022002 APPLICATOR (CA10) WITH UC200 OR EQUIVALENT PRESS
 - D. UNI-M APPLICATOR (MRSP1516JM9D) WITH UC200 OR EQUIVALENT PRESS
 - E. UNI-M APPLICATOR (MRSP1516JVD) WITH UC200 OR EQUIVALENT PRESS

3. WIRE STRIP LENGTH: $13/32'' \begin{smallmatrix} +1/32 \\ -0 \end{smallmatrix} [10,0 \begin{smallmatrix} +0,8 \\ -0 \end{smallmatrix}]$

4. MATERIAL:
A. STAMPING: COPPER, TIN PLATED
B. HOUSING: POLYPROPYLENE, COLOR CODED
C. COLOR CODE CONFORMS TO DIN STANDARD
5. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT
6. FOR TOLERANCING REFER TO DIN 46228 PART 4



PART NUMBER		SEE TABLE	
TITLE		FERRULES WITH SLEEVES ON CONTINUOUS REEL (DIN)	
ITEM REVISION NAME		CUSTOMER DRAWING	
DATASET FILE NAME			
N41737BA/15 N41737BA_DC/15A			
 THIRD ANGLE PROJECTION			
MATERIAL		DRAWING NUMBER	
SEE NOTES		A41737	
DRAWN BY	DATE	CHK	SHEET
DAW	01-07	LCA	N.T.S.
SHEET 1 OF 1		A	

B

B

A

A-SIZE CUSTOMER