

YGHC29C26 Compression Grounding C-TAP Connector

By Burndy

Catalog # [YGHC29C26](#)

Copper Compression C Connector, 3/0 AWG(Str) - 250 kcmil, 1/2" or 5/8" Rod (Run) & 6 AWG(Sol) - 2/0 AWG(Str) (Tap)



Features

- Irreversible compression ground tap figure C connector
- C-shaped opening permits placing two continuous parallel cables into conductor groove
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial Cables

Specifications

| | |
|---|--|
| Buy American Compliant | No |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Industry Standard(s) | Direct Burial |
| Certification - ETL | No |
| Standards - Industry Standards Met | <ul style="list-style-type: none"> • UL467 • IEEE 837 • UL468A-468B |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | Yes |
| UL Listed | Yes |
| Certification - UL Listed Direct Burial | Yes |

Conductor

| | |
|------------------------------------|---|
| Conductor - Rod Run | <ul style="list-style-type: none"> • 1/2 in • 5/8 in |
| Conductor - Rod Run Range | 1/2 in-5/8 in |
| Conductor - Copper Solid Tap | <ul style="list-style-type: none"> • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG |
| Conductor - Copper Solid Tap Range | 6 AWG-3/0 AWG |
| Conductor - Copper Str Run | <ul style="list-style-type: none"> • 3/0 AWG • 4/0 AWG |

| | |
|----------------------------------|---|
| Conductor - Copper Str Run Range | <ul style="list-style-type: none"> • 250 kcmil |
| Conductor - Copper Str Tap | <ul style="list-style-type: none"> • 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG |
| Conductor - Copper Str Tap Range | 7 AWG-2/0 AWG |

Configuration

| | |
|--|-----|
| Physical Attribute - Number of Crimps Required | 1 |
| Connector Type | Tap |

Dimensions

| | |
|---------------------------------|------------|
| Dimension - L Length Overall mm | 19 mm |
| Dimension - Height fraction | 1-32/33 in |
| Dimension - Height inch | 1.97 in |
| Dimension - Height mm | 50 mm |
| Dimension - B Length fraction | 0.75 in |
| Dimension - B Length inch | 0.75 in |
| Dimension - Length Overall inch | 0.75 in |

General

| | |
|-------------------|-----------------|
| Die Index | 997 |
| Trade Name | HYTAP™ |
| Sub Brand | HYGROUND, HYTAP |
| Plated | N |
| Type | Taps |
| UPC 12 Digit | 781810221044 |
| UPC 14 Digit GTIN | 00781810221044 |
| Material | Copper |
| Plating Type | Unplated |
| UPC | 781810221044 |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

Carton Quantity 50
Pallet Quantity 9250

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YGHC29C26-SPEC-EN | REV 12/2025