

Compression Lugs

Two Hole - Long Barrel

Features

- Produced from high conductivity copper tubing and suitable for heavy duty applications
- Tin-plated to provide corrosion resistance
- Color coded

Applications


- Listed for 35 KV maximum when properly installed
- Ideal for direct burial in earth or concrete and grounding applications

Standard Material

- Copper

Standard Finish

- Tin plated



Catalog Number	UPC	Wire Size	Color Code	Bolt Size	Unit Carton	Ship Case	Weight/ Case	Inches		C = Hole Spacing
								A	B	
3201	81812	#8	Red	1/4"	100	1000	23	2.19	.42	.625
3202	81633	#6	Blue	1/4"	100	1000	26	2.19	.42	.625
3203	81635	#4	Gray	1/4"	100	1000	31	2.36	.49	.625
3205	81636	#2	Brown	1/2"	50	500	39	4.25	.807	1.75
3206	81638	1/0	Pink	3/8"	25	250	32	4.40	.74	1.75
3207	81639	2/0	Black	3/8"	100	1000	34	4.61	.81	1.75
3208	81701	3/0	Orange	1/2"	20	200	33	4.69	.90	1.75
3209	81641	4/0	Purple	1/2"	10	100	21	4.72	1	1.75
3209A	81642	250 MCM	Yellow	1/2"	10	100	27	4.95	1.09	1.75
3209B	81643	300 MCM	White	1/2"	10	100	31	5.31	1.19	1.75
3210	81644	350 MCM	Red	1/2"	10	100	37	5.39	1.28	1.75
3210A	81645	400 MCM	Blue	1/2"	5	50	23	5.47	1.39	1.75
3211	81646	500 MCM	Brown	1/2"	5	50	32	5.79	1.72	1.75
3211A	81647	600 MCM	Green	1/2"	5	50	41	5.79	1.72	1.75
3212	81648	750 MCM	Black	1/2"	5	50	56	6.30	1.90	1.75