



**SKU:** PBTD-11-350-M

**UPC:** 0783669001037

**Features & Benefits:**

**Description:** Nimbus Insulated Aluminum Multi-Tap Connector, Conductor Range 350-6, 11 Ports, Dual Sided Entry, Mountable, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Mounting Hole Type	Thru
Number of Conductors	11
Number of Mounting Holes	2
Number of Poles	1
Number of Ports / Wireways	11
Number of Usable Ports	11
Replacement Part(s)	PORTPLUG-350, SCREWCAP-350

### Dimensions

Drive Size Main	5/16
Drive Type Main	Internal Hex
Height (IN)	2.588
Height BX (IN)	3.75
Height (mm)	65.7352
Length (IN)	15.246
Length (mm)	387.2484
Max Insulation OD (IN)	0.86
Max Insulation OD (mm)	21.844
Mounting Hole Diameter (IN)	0.321
Mounting Hole Spacing (IN)	13.872
Mounting Hole Spacing (mm)	352.3488
Weight (LB)	2.71138375726974
Weight BX (LB)	3.0335
Width (IN)	2.578
Width BX (IN)	6.5
Width (mm)	65.4812

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	Plastisol
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum



## Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

## Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	11/16
Wire Binding Torque	275

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366900103

## Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	350 kcmil - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Flex Conductor Range	NA

## Voltage

Voltage Rating	600 V
----------------	-------

## Color

Cap Color Main	Black
Cap Color Tap	Black
Color	Black

## Environment and Temperature

Environmental Conditions	Cold temperature rated to -45°C
--------------------------	---------------------------------



Flammability Rating  
Temperature Rating

Insulation rated per UL 94  
90°C