



**SKU:** AU-0

**UPC:** 0783669000665

**Features & Benefits:**

**Description:** Aluminum Mechanical Lug, Conductor Range 1/0-14, 2 Ports, 1 Hole, 1/4in Bolt Size, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Contains DE-OX®            | No         |
| Mounting Hole Type         | Thru       |
| Number of Conductors       | 2          |
| Number of Mounting Holes   | 1          |
| Number of Poles            | 1          |
| Number of Ports / Wireways | 2          |

### Dimensions

|                             |         |
|-----------------------------|---------|
| Dimension G (IN)            | 0.422   |
| Drive Size Main             | NA      |
| Drive Type Main             | Slotted |
| Height (IN)                 | 0.794   |
| Height BX (IN)              | 2.25    |
| Height (mm)                 | 20.1676 |
| Length (IN)                 | 1.469   |
| Length (mm)                 | 37.3126 |
| Mounting Hole Diameter (IN) | 0.272   |
| Mounting Hole Diameter (mm) | 6.9088  |
| Mounting Hole Spacing (mm)  | 0       |
| Tang Length (IN)            | 0.844   |
| Tang Length (mm)            | 21.4376 |
| Tang Thickness (IN)         | 0.187   |
| Tang Thickness (mm)         | 4.7498  |
| Tang Width (IN)             | 1.125   |
| Tang Width (mm)             | 28.575  |
| Weight (LB)                 | 0.137   |
| Weight BX (LB)              | 1.8816  |
| Width (IN)                  | 1.125   |
| Width BX (IN)               | 5       |
| Width (mm)                  | 28.575  |

### Material and Finish

|                    |          |
|--------------------|----------|
| Conductor Material | Copper   |
| Connector Finish   | Tin      |
| Insulation         | NA       |
| Material           | Aluminum |



## Voltage

Voltage Rating

35 kV