

EMT/Rigid Clampbacks

Hot Dip Galvanized - Malleable Iron

Features

- Hot dip galvanized for added durability and corrosion protection

Applications

- For use in wet or dry locations in conjunction with malleable Rigid conduit straps to create space between conduit and mounting surface

Standard Material


- Malleable iron

Standard Finish

- Hot dip galvanized



Conforms to finish thickness
ASTM A123/123M
UL 2239
RoHS
Fed. Spec. A-A-50553
NEMA FB 1



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
481HDG	86601	1/2"	25	250	15	2.06	1.01	.44
482HDG	86602	3/4"	25	250	23	2.44	1.20	.48
483HDG	86603	1"	25	250	35	2.92	1.31	.56
484HDG	86604	1-1/4"	10	100	21	3.41	1.49	.67
485HDG	86605	1-1/2"	10	100	27	3.78	1.52	.76
486HDG	86606	2"	5	50	22	4.73	1.92	.80
487HDG	86607	2-1/2"	---	25	14	5.48	2.42	.80
488HDG	86608	3"	---	10	9	6.66	2.63	.83
489HDG	86609	3-1/2"	---	12	10	7.12	2.87	1.03
489AHDG	86610	4"	---	18	21	8.43	3.12	1.09
489BHDG	86611	5"	---	10	21	10.78	3.68	1.30
489CHDG	86612	6"	---	10	29	12.68	3.96	1.89